

# MAXHUB



## MAXHUB UC P15

Full HD PTZ Camera with Clear Video Imagery for Medium to Large Meeting Room



Smooth Full HD Video with 60 fps maximum frame rate



Experience life-like video even in challenging meeting room illumination



Supports multiple camera control methods (IR Remote/Serial/IP/USB)



Plug-n-play simplicity; works with common UC applications



# EXCEPTIONALLY SMOOTH & CRYSTAL-CLEAR VIDEO

Full-HD video at 60 fps for studio-quality experience

Maximum frame rate 1080P @ 60 fps





# EXCEPTIONALLY SMOOTH & CRYSTAL-CLEAR VIDEO

Lifelike and natural images even in dimly lit meeting rooms.

Super low-light performance CMOS sensor |

2D/3D denoising algorithm |

High SNR for noise-free images



2D & 3D DNR

# RAZOR-SHARP FOCUS—FROM WIDE SHOTS TO CLOSEUPS


Professional-grade optical technology delivers superior wide-angle video and ultra-sharp close-ups. Even in large boardrooms, 12x optical and 16x digital zoom can reach the farthest corners, while responsive autofocus keeps zoomed images sharp and clear.

Total 192x zoom from wide-angle 85.2° diagonal FOV lens |

Fast F1.2-F2.8 lens aperture |

Responsive autofocus 12x optical zoom |

16x digital zoom








## ADAPTIVE PTZ MOVEMENT FOR PRECISION IMAGES

The UC P15 automatically adjusts pan and tilt speeds based on the zoom level, with 0.1° preset accuracy for more precise images. The camera's 90° tilting angle further enhances coverage and overhead viewing support.


Tilt  $-30^{\circ} \sim +90^{\circ}$  (overhead view) | Pan  $\pm 170^{\circ}$  |

Adaptive pan & tilt speed based on zoom level (x1 to x12) |


0.1° preset accuracy | Up to 255 presets



HFoV 72.5°



Tilt -30° ~ +90°



Pan ±170°

## ADAPTIVE PTZ MOVEMENT FOR PRECISION IMAGES

UC P15 automatically adjusts pan and tilt speeds based on the zoom level, with 0.1° preset accuracy for more precise images. The camera's 90° tilting angle further enhances coverage and overhead viewing support.

Tilt -30° ~ +90° (overhead view) | Pan ±170° |

Adaptive pan & tilt speed based on zoom level (x1 to-x12) |

0.1° preset accuracy | Up to 255 presets



# LOCKABLE USB TYPE-C INTERFACE FOR A SECURE CONNECTION

The latest USB 3.0 features a locking screw that securely connects the USB-C cable to the camera, preventing accidental disconnection. Backward compatible with the USB 2.0 standard, the ultra-fast USB 3.0 interface supports all major UC applications.

USB Type-C cable with locking screw mechanism

USB audio, video, and control under standard UVC  
v1.1~1.5 protocol



# EFFORTLESS VIDEO STREAMING

With the integrated IP streaming encoder, streamed content can be broadcast live on popular platforms such as YouTube, Vimeo, Facebook, and Twitch.

Built-in RTSP/RTMP encoder





# ONE CABLE FOR EVERYTHING

The one-cable power-over-ethernet (PoE) solution reduces installation costs and allows for flexible deployment in a variety of scenarios. Supports multiple power input for added redundancy.

Multiple power inputs: 12V DC power, PoE



# MULTIPLE CONTROL OPTIONS

Tailor the camera operation based on the environment with multiple control options including web interface, software & USB, IP network, serial control, and infrared remote control.



VISCA, PELCO, UVC, and ONVIF protocol supported

IR Controller | Web/Software & USB

IP Network | Serial Controller (RS232 & RS485)







# DEVICE MANAGEMENT AT YOUR FINGERTIPS

Use MAXHUB ALIGN to update and optimize the status of your video meeting devices, and fine-tune camera performance to look your best on video calls. Device can be managed remotely for your hybrid meeting needs through the MAXHUB Pivot.

# SUPPORTS POPULAR VIDEO CONFERENCING PLATFORMS

Works with what you have. The UC P15 is compatible with Zoom, Microsoft Teams, RingCentral, Cisco Webex, Google Meet, and other popular platforms.

A blue circle with the word "Zoom" in white text.

Zoom

A dark blue circle with the words "Microsoft Teams" in white text.

Microsoft  
Teams

An orange circle with the word "RingCentral" in white text.

RingCentral

A light blue circle with the words "Cisco Webex" in white text.

Cisco  
Webex

A yellow circle with the words "Google Meet" in white text.


Google  
Meet



# SCALABLE FROM MEDIUM TO LARGE- ROOM APPLICATIONS

The bundled solution with UC BM35 allows for deployment and collaboration in a wide range of large spaces.

## Bundled solution with UC BM35



### Full HD 12x Zoom PTZ Camera (UC P15)


Zoom	12x Optical Zoom, 16x Digital Zoom (Total 196x)
Resolution	Full HD 1080P
DFOV	85.2°

### Dual Daisy Chain Speakerphone (UC BM35)


Voice Pickup	Up to 12m
Microphones	16-mic array combined
Daisy chain	BT wireless cascading

# USE CASE


## Large meeting room



## Teaching and learning



## Small studio streaming





# PERFORMANCE YOU CAN COUNT ON

Never miss out on a crucial meeting. Phenomenal quality, backed by a 3-Year Hot Swap Warranty, gives you confidence that UC P15 will be ready when you are.



CONTACT SALES

Interested in the MAXHUB UC solution?

Get in touch with a member of our sales team by emailing [sales@maxhub.com](mailto:sales@maxhub.com)



# SPECIFICATION

## Camera

- Full HD 1/2.8", CMOS, 2.07M Pixel
- Video System: 1080P60, 1080P50, 1080P30, 1080P25, 720P60, 720P50
- Progressive Scanning
- 12x Optical Zoom
- 192x Total Zoom (16x Digital)
- Lens: f3.5mm ~ 42.3mm, F1.8 ~ F2.8
- Min. Illumination: 0.5Lux @ (F1.8, AGC ON)
- Shutter: 1/30s ~ 1/10000s
- White Balance: Auto, Indoor, Outdoor, One Push, Manual, VAR
- Backlight Compensation
- 2D&3D Digital Noise Reduction
- Video S/N: ≥55dB
- Horizontal Angle of View :72.5°~ 6.9°
- Vertical Angle of View: 44.8°~ 3.9°
- Diagonal Angle of View: 85.2°
- Pan: ±170°
- Tilt: -30° (down) +90° (up)
- Pan Speed Range: 2.7° ~ 35.7°/s
- Tilt Speed Range: 2.7° ~ 31.5°/s
- Horizontal & Vertical Flip
- Support Image Freeze
- Number of Preset: up to 255
- Preset Accuracy: 0.1°

## USB Features

- Operating System: Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android
- Video Format: YUY2, MJPEG, H.264
- Resolution: Max 1080P@60fps
- Type-C USB 3.1 Gen 1, backward compatible with USB 2.0
- UVC 1.1~1.5
- UAC 1.0

## Physical Specifications

- Camera Dimension L×H×D : 144 x 144 x 167.9 (mm)
- Net Weight:1.41Kg
- Package Dimension L×H×D: 230 x 230 x 250 (mm)
- Gross Weight: 2.5Kg

## Network Features

- Video Compression:H.264/MJPEG
- Dual Video Stream
- Main Stream Resolution: 1920x1080, 1280x720, 1024x576,960x540,640x480,640x360
- Sub Stream Resolution: 1280x720, 1024x576, 720x480,720x408,640x360,320x240, 320x180
- Video Bit Rate: 32Kbps ~ 102400Kbps
- Bit Rate Type: Variable Rate, Fixed Rate
- Frame Rate: 50Hz: 1~ 50fps, 60Hz: 1~ 60fps
- Audio Compression: AAC
- Audio Bit Rate: 96Kbps, 128Kbps, 256Kbps
- Support protocols: TCP/IP, HTTP, RTSP, RTMP, ONVIF, DHCP, Multicast, etc.

## Power

- Simultaneous power input: Power jack DC 12V/ USB DC 5V/ PoE (802.3af)
- Current Consumption: 12V 1.0A (Max) / 5V 1.5A (Max)
- Power Consumption: 12W (Max)

## Input/ Output Port

- USB 3.1 Type-C
- HDMI 1.4b
- RJ45, 10/100Mbps Ethernet
- 3.5mm Jack, Line In
- RS232, 8pin mini DIN
- RS485, 2-core Phoenix Port
- Power Jack, EITA type DC IN 12V

## Compatible Applications

Support Major VC Software including ZOOM, Microsoft® Teams, Google Meet, Google Hangouts, Cisco WebEx®, RingCentral, etc.,

## Package Contents

- UC P15 Camera
- Lens Cover
- USB 3.0 Cable
- Power Adaptor
- Remote Control
- Wall-mount bracket
- Mounting Screw Set
- User Manual

## Warranty

- Camera 3 Years Hot Swap
- Accessories 1 Year