

BenQ



BenQ Board RE04D

Miliki semua perangkat yang Anda butuhkan untuk pelajaran interaktif yang efektif dengan interactive whiteboard.

RE6504D
TKDN+BMP = **52,23%**

RE7504D
TKDN+BMP = **52,16%**


RE8604D
TKDN+BMP = **50,38%**



RE04D



Android
Android 13
The latest & most secure update



Octa Core SoC
Excellent performance



40W Built-in Speaker
20W x 2 speakers



40 Touch Points
Unleash your creativity



5-in-1 Type-C 65W PD
Display, audio, touch, data, and 65W power charging

Memanfaatkan kekuatan Google

BenQ Board bersertifikasi EDLA menggabungkan layanan Google dengan perangkat keras dan perangkat lunak BenQ yang selalu dapat diandalkan.



Pustaka aplikasi yg luas

Instal aplikasi pendidikan langsung dari Google Play untuk pelajaran yang lebih interaktif.



Masuk ke layanan Google

Mengakses Google Core Services yang penting seperti Google Drive dan Meet.



Editor Google Documents

Membuka file pelajaran dengan cepat dengan aplikasi Google apa pun pada display layar sentuh yang besar.

Spesifikasi Sertifikat



**SIAA Certified
for Touchscreen**
Antimicrobial property,
safety, and appropriate



**Germ-Resistant,
Eyecare**
Safe-to-Touch for touchscreen
Eyecare for Low Blue Light,
Flicker Free



IP5X Dust Proof
To ensure consistent operation
IEC standard 60529



Energy Star
Lower energy bills

Spesifikasi

Display	
Diagonal Size	65", 75", 86"
Display Technology	Zero Bonding
Backlight / Panel Type	DLED / IPS
Aspect Ratio	16:9
Resolution	3840 x 2160 (4K)
Brightness (typical)	450 cd/m2
Contrast Ratio (typical)	1200:1
Contrast Ratio (dynamic)	30000:1
LCD Viewing Angle	178°/178°
Panel Refresh Rate	60 Hz
Response Time	8 ms
Panel Bit	10-bit
Panel Lifespan	50,000 hours
Operating Hour	18/7
Glass Hardness	9H
Glass Type	Heat-tempered 3.2 mm
Germ-Resistant Technology	Nano-ionic silver
Panel Surface	Anti-Glare, 65"/75" Haze: 25%, 86" Haze: 28%
Display Orientation	Landscape

Sensors	
Light Sensor	x1
IR receiver	x1

Touch	
Touch Technology	Precision IR
Accuracy	±1.0 mm (middle 90% touch area)
Max Touch Points	40 for Windows*, 32 for Android
Touch Resolution	32767 x 32767 px
Object Recognition Range	≥ 3.5 mm
Touch Response Time	< 5 ms
Touch Interface	USB-B 2.0 x 2
Compatibility	Windows10/Windows8/ Windows7/ macOS/Linux/ Android/Chrome OS

Computing	
Operating System	Android 13 (Tiramisu)
CPU	Octa-Core (A73 x 4 + A53 x 4)
GPU	MaliTM-G52 MP8
Memory	8GB
Storage	64GB

Audiovisual	
Built-in Speaker	40 Watts (20 W x 2)
Built-In Camera	Optional

Power	
Power Supply	AC 100 to 240V, 50 to 60 Hz
Power consumption (typical)	65": 66.7W; 75": 73.9W; 86": 106.8W

SOFTWARE/SOLUTIONS	
Device Management Solution	DMS 3.0
Account Management Solution	AMS
Broadcasting Solution	X-Sign Broadcast
Wireless Casting Solution	InstaShare 2
Whiteboarding Solution	EZWrite 6
Floating Tool	Yes
Class Recording	Yes
Scalable canvas	Yes
Handwriting recognition	49 Languages
Co-annotation via intranet	Cloud Whiteboard
Co-annotation via internet	EZWrite 6 Web (Web browser)

DISPLAY LANGUAGES	
English/French/German/Dutch/Polish/Russian/ Czech/Danish/Swedish/Italian/ Romanian/Finnish/ Norwegian/Greek/Hungarian/Spanish/Portuguese/ Turkish/ Traditional Chinese/Simplified Chinese/ Arabic/Japanese/Thai/Persian/Korean/ Vietnamese/ Indonesian/Hebrew (28L)	

ACCESSORIES	
Remote Control, Power Code (By Region), Stylus x 2, Quick Start Guide, Regulation Sheet, Touch USB Cable, HDMI Cable, VGA (D-sub 15pin) Cable, Type-C Cable, Wall Mount	

CONNECTIVITY	Front	Rear	Bottom
HDMI In 2.0	x1	x2	
HDMI Out 2.0		x1	
Display port 1.2a		x1	
VGA In			x1
PC Audio In			x1
USB-A 3.0 (High speed data transfer & power supply)	x2		
USB-A 2.0		x2	
USB-B 3.0 (Touch)	x1	x1	
USB Type-C 3.0 (5-in-1, 65W PD)	x1		
USB Type-C 2.0 (Data transfer)		x1	
Mic In (3.5 mm)	x1		
RS232			x1
Earphone (3.5 mm)	x1		
SPDIF (optical)			x1
Power (AC) Inlet			x1
OPS Slot		x1	
SD Card Slot (*with protecting cover)		x1	
Wake-on-LAN		Yes	
LAN In/Out (RJ45)	x2 OPS: 10/100/1000 Mbps; Android: 10/100/1000 Mbps		
Wi-Fi 6.0 (*with protecting cover)	Optional		
Bluetooth 5.2	Optional		

Model	RE6504D	RE7504D	RE8604D
Dimension (WxHxD)	1482.1 × 907.3 × 87.7 mm / (Without Packing / With Packing)	1716.5 × 1041.6 × 87.7 mm / 1860 × 1125 × 185 mm	1962.4 × 1174.9 × 87.1 mm / 2095 × 1265 × 185 mm
Net Weight/Gross Weight	36.4 kg/49.4 kg	50.2 kg/64.9 kg	63.4 kg/80.2 kg
VESA Mount/Screws	600 x 400 mm/ 4 - M8 x 25mm	800 x 400 mm/ 4 - M8 x 25mm	800 x 600 mm/ 4 - M8 x 25mm